CONNECTION HEAD - type XD-ADdia (type XD-ADwin + ST0028)



33

Kg
~0.80 Kg

FTZU 03 ATEX 0074U
II 2 G Ex db II C Gb
II 2D Ex tb IIIC Db

IECEx FTZU 14.0003U
Ex db II C Gb
Ex tb IIIC Db

	XD-AD	ORDERING CODE				SPECIFICATION
(1)	Display type	dia				Programmable loop powered LCD display - ST0028
(2)	Material of elements	4				Metal parts - stainless steel; seals - silicone rubber
(3)	Cable gland thread D_2/ D_3 Please choose two variants of thread, separately for D_2 and D_3 **For example: XD-ADdia-4-M2/CD..**		M2			M20x1.5 6H
			G2			G½; BSP½ (without cert.)
			G3			G¾; BSP¾ (without cert.)
			G4			G⅜; BSP⅜ (without cert.)
			N2			½NPTmod - modified ac. to OIT-17/03
			N3			¾NPTmod - modified ac. to OIT-17/03
			CD			CD = closed (D_3 only)
(4)	Type of process thread D_1			M2		M20x1.5 6H
				M24		M24x1.5 6H
				M27		M27x2 6H
				G2		G½; BSP½ *
				G3		G¾; BSP¾ *
				G4		G⅜; BSP⅜ *
				N2		½NPTmod - modified ac. to OIT-17/03
				N3		¾NPTmod - modified ac. to OIT-17/03
(5)	Symbol of hole d_1 diameter				6	Ø6 $^{+0.04}_{-0.05}$
					6.1	Ø6.1 H8
					8	Ø8 $^{+0.1}_{+0.02}$
					8.1	Ø8.1 H8
					9.6	Ø9.6 H8
					10	Ø10 $^{+0.1}_{+0.02}$
					10.1	Ø10.1 H7
					12.8	Ø12.8 H7
					13	Ø13 (non flameproof)
					15.1	Ø15.1 H7
					M16	M16x1.5 6H
						or other hole on request (non flameproof)
(8)	Paint type				C	Creodur - Rafil
					SE	Spray epoxy
					SPU	Spray polyurethane on (SE) layer
(9)	Paint colour					al alu natural colour (only Creodur - Rafil)
						yc RAL 1007 daffodil yellow
						ys RAL 1003 signal yellow
						bs RAL 5005 signal blue
						sb RAL 5015 sky blue
						sg RAL 7032 pebble grey
						gr RAL 7035 light grey
						ag RAL 9002 grey white
						sh RAL 9006 white aluminium
						gs RAL 9007 grey aluminium
						cw RAL 9010 pure white

CAUTION: Certificates are for head only. For more details see catalogue cards of XD-A…

Maine features:

- material of body and cover - aluminium pressure die-castings, max 0.5%Mg
- service temperature Connection Head: T_{serv}= -50÷85ºC - silicone rubber
  T_{serv}= -20÷85ºC - fluoroelastomer rubber
- maximum space for transmitter: Ø52x30mm
- coating: yellow chromating (optionally) and chemically resistant paint (outside only)

Material: aluminium EN AC 44200mod or EN AC 46000.

EN AC 46000 - the kind of material meets the requirements for use in potentially explosive areas.

EN AC 44200mod - the kind of material meets the requirements for use in potentially explosive areas.
In additon, it is characterized by increased strength (pressure) parameters, while at the same time shows reduced copper (Cu) concentration.

Caution:
The type EN AC 44200mod - available for certified products ATEX, IECEx, FM and CSA.
The type EN AC 46000 - available only for certified products ATEX and IECEx.

Ordering example:

(1)	(10)	(2)		(3)		(4)	(5)		(8)	(9)
XD-AD	dia	2	-	M2/CD	-	M24/8.1		-	SE	sh

* in this case hole d1 must be flameproof (for arrange flameproof joint with sensor measuring insert). Flameproof possible only for gas.
For Ex tb - dust (for thread D1) require certification of the complete equipment.