

# STANDARD TERMINAL BLOCKS

	M6S-VS9 for spring loaded version	M6S-VL6	M6S-VS10L
	19 20	19 20	19 20
Place to install	„M” type connection heads with 19 or 20mm mounting holes spacing		
Type of installation	Directly fixed to the connection head by M2.5 or M3 screws	Directly fixed to the connection head by M2.5, or M3 screws or springing disk	Directly fixed to the connection head by M2.5 or M3 screws
Material of block	Steatite C220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	4		
Max. diameter of inside wire	Ø1.35mm	Ø0.5mm	Ø1mm
Way of connection inside wire to the terminals	By screwing	By soldering	By soldering
Protection Method	–	–	EExia ac. to EN 50020
	<b>ORDERING</b>		
Type	M6S-VS9-2 to M6S-VS9-4	M6S-VL6-2 to M6S-VL6-4	M6S-VS10L-2 to M6S-VS10L-4
Number of terminals	2 to 4		
<b>Ordering example:</b>	<b>Terminal block M6S-VS9-2</b>	<b>Terminal block M6S-VL6-2</b>	<b>Terminal block M6S-VS10L-4</b>
<i>Unit for fixing to the connection head</i>			
NAME	TYPE		
Mounting kit	KMD-19 or KMD-20	KMD-19 or KMD-20	KMD-20X
	<i>Unit for spring loaded version</i>	<i>Unit for spring loaded version</i>	–
Mounting kit	KMF-1	KMF-1	–
Springing disk	MSD1-d d = 1,5; 3; 4,5; 6	MSD1-d d = 1,5; 3; 4,5; 6	–
Bush springing disk	MSDB1-d d = 1,5; 3; 4,5; 6	MSDB1-d d = 1,5; 3; 4,5; 6	–