

STANDARD TERMINAL BLOCKS

	B16S-G5L	A1S-HS2	A1S-G6
	33	46	46
Place to install	„B” type connection heads with 33mm mounting holes spacing	„A” type connection heads with 46mm mounting holes spacing	„A” type connection heads with 46mm mounting holes spacing
Type of installation	Directly fixed to the connection head by M4 screws		
Material of block	Steatite C220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	6	4	4
Max. diameter of inside wire	Ø1.2mm	Ø3mm	Ø1.2mm
Way of connection inside wire to the terminals	By soldering	By screwing	By screwing
	ORDERING		
Type	B16S-G5L-2 to B16S-G5L-6	A1S-HS2-2 to A1S-HS2-4	A1S-G6-2 to A1S-G6-4
Number of terminals	2 to 6	2 to 4	2 to 4
Ordering example:	Terminal block B16S-G5L-6	Terminal block A1S-HS2-4	Terminal block A1S-G6-2
<i>Unit for fixing to the connection head</i>			
NAME	TYPE		
Mounting kit	KBD-1		
	-	-	<i>Unit for spring loaded version</i>
Mounting kit	-	-	KAF-1
Springing disk	-	-	ASD1-d d = 4.5;6;8
Bush springing disk	-	-	ASDB1-d d = 4.5;6;8

STANDARD
TERMINAL BLOCKS

08