

	SBd-M5S-VS3L	SBd-B1S-FL1	
	20	33	
Place to install	„M” type connection heads - with 20mm mounting holes spacing	„B” type connection heads - with 33 mm mounting holes spacing	
Type of installation	Springing fixed to the connection head by M3 screws	Springing fixed to the connection head by M4 screws	
Way of connecting with measuring insert	By pressing		
Diameter of measuring insert	d = 3; 4.5; 6 [mm]	d = 3; 4.5; 6; 8 [mm]	
Max. number of terminals	4		
Max. diameter of inside wire	Ø1mm		
Way of connecting inside wire to the terminals	By soldering		
Material of connecting wire	-	Ag (Ø0,8); J type (Ø1); K type (Ø1)	
	ORDERING		
Type	SBd-M5S-VS3L-2 to SBd-M5S-VS3L-4	SBd-B1S-FL1-2 to SBd-B1S-FL1-4	SBd-B1S-FL1-3
D [mm]	3; 4.5; 6	3; 4,5; 6; 8	
Number of terminals	2 to 4	2, 4	3
Material of connecting wire	-	Ag; J; K	Ag
Ordering example	Spring loaded terminal block SBØ6-M5S-VS3L-4	Spring loaded terminal block SBØ6-B1S-FL1-4Ag	