

	B15S-VS2Lr	B15S-VS2
Place to install	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing
Type of installation	Riveted to the springing disk by Ø3mm rivets	Riveted to the springing disk by Ø3mm rivets
Material of block	Steatite C220 ac. to IEC 60672-3	Steatite C220 ac. to IEC 60672-3
Material of terminals	Material of...*	Nickel - plated brass
Max. number of terminals	6	6
Max. diameter of inside wire	Ø1.2mm	Ø1.2mm
Way of connection inside wire to the terminals	By screwing / by welding	By screwing
	<b>ORDERING</b>	<b>ORDERING</b>
Type	B15S-VS2Lr-2* to B15S-VS2Lr-6*	B15S-VS2-2 to B15S-VS2-6
Number of terminals	2 to 6	2 to 6
<b>Ordering example:</b>	<b>Terminal block B15S-VS2Lr-6mn</b>	<b>Terminal block B15S-VS2-6</b>
	<i>Unit for fixing to the connection head</i>	<i>Unit for fixing to the connection head</i>
<b>NAME</b>	<b>TYPE</b>	<b>TYPE</b>
Mounting kit	–	–
	<i>Unit for spring loaded version</i>	<i>Unit for spring loaded version</i>
Mounting kit	KBF-3	KBF-3
Springing disk	BSD2-d d = 3; 4.5; 6; 8	BSD2-d d = 3; 4.5; 6; 8
Bush springing disk	BSDB2-d d = 3; 4.5; 6; 8	BSDB2-d d = 3; 4.5; 6; 8

\* ... terminal body - nickel-plated brass  
... terminal lug - stainless steel (n), copper (m)