

STANDARD TERMINAL BLOCKS

	B10S-G5	B10S-G5Lr	B10S-HS21
Place to install	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing
Type of installation	Riveted to the springing disk by Ø3mm rivets	Riveted to the springing disk by Ø3mm rivets	Riveted to the springing disk by Ø3mm rivets
Material of block	Steatite C220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	6	6	6
Max. diameter of inside wire	Ø1.2mm	Ø1.2mm	Ø1.2mm
Way of connection inside wire to the terminals	By screwing	By soldering	By screwing
	ORDERING		
Type	B10S-G5-2 to B10S-G5-6	B10S-G5Lr-2 to B10S-G5Lr-6	B10S-HS21-2 to B10S-HS21-6
Number of terminals	2 to 6	2 to 6	2 to 6
Ordering example:	Terminal block B10S-G5-6	Terminal block B10S-G5Lr-6	Terminal block B10S-HS21-6
	-	-	-
NAME	TYPE		
Mounting kit	-	-	-
<i>Unit for spring loaded version</i>			
Mounting kit	KBF-4	KBF-4	KBF-4
Springing disk	BSD3-d d = 3; 4.5; 6; 8	BSD3-d d = 3; 4.5; 6; 8	BSD3-d d = 3; 4.5; 6; 8
Bush springing disk	BSDB3-d d = 3; 4.5; 6; 8	BSDB3-d d = 3; 4.5; 6; 8	BSDB3-d d = 3; 4.5; 6; 8