



(1)	A	ORDERING CODE	SPECIFICATION				
	Material of elements	3	Cable gland - nickel - plated brass; other metal parts - stainless steel; seals-oil resistant rubber (-40...100°C)				
		4	Cable gland - nickel - plated brass; other metal parts - stainless steel; seals - silicone rubber (-40...150°C)				
(3)	Cable gland thread	M2	M20x1.5				
		G2	G½				
		N2	½NPT (empty thread only)				
		P1	Pg16				
(4)	Type of cable gland seal	A	Without notches				
		B	With notches				
		X	No gland, threaded hole only				
(5)	Type of process thread D ₁ /d ₁		D₁ [ø]	d₁ [ø]	l₁	d4	
		1	*	Ø13	-	-	M6
		2	STANDARD	Ø22.3	Ø21	-	M6
		3	STANDARD	Ø22.8	Ø21	-	M6
		4	*	Ø26.8	Ø21	-	M6
		5	STANDARD	Ø32.5	Ø28	-	M6
		6	STANDARD	M24x1.5	Ø15	17	-
		7	STANDARD	M24x1.5	Ø21	17	-
		8	STANDARD	G½	Ø14	17	-
		9	STANDARD	G¾	Ø21	17	-
		10	*	½NPT	-	17	-
		11	*	¾NPT	-	17	-
		12	*	Ø15,3	Ø13	-	M6
		13	*	Ø15,5	Ø12,5	-	M6
		14	*	Ø15,5	Ø13	-	M6
		15	*	Ø28,8	Ø21	-	M6
		16	*	Ø24,8	Ø21	-	M6
		17	*	Ø22,5	Ø21	-	M6
		18	*	M12x1	Ø9	17	-
19	*	M32x1,5	Ø21	17	-		
(6)	Side screw d4=2xM6	a	Pan head screw made of steel				
		b	Cup - point set screw with hex socket made of steel				
		c	Pan head screw made of brass				
		e	Pan head screw made of stainless steel				
		f	Cup - point set screw with hex socket made of stainless steel				
		x	No side screw				
(7)	Cover closure	NS	Screws without leaden seal holes				
		LS	Screws with leaden seal holes				
(8)	Paint type	P	Polyester				
		E	Epoxy				
		C	Creodur - Rafil				
(9)	Paint colour	al	alu natural colour (only Creodur - Rafil)				
		yc	RAL 1007 daffodil yellow				
		ys	RAL 1003 signal yellow				
		bs	RAL 5005 signal blue				
		sb	RAL 5015 sky blue				
		sg	RAL 7032 pebble grey				
		gr	RAL 7035 light grey				
		ag	RAL 9002 grey white				
		sh	RAL 9006 white aluminium				
		gs	RAL 9007 grey aluminium				
		cw	RAL 9010 pure white				
		wa	white aluminium (substitute of Cal, only Polyester)				

Main features:

- material of body and cover - aluminium pressure die-castings
- cable gland washer - zinc-plated press steel
- temperature range: -40+100°C - oil-proof rubber, -40+150°C - silicone rubber
- maximum space for transmitter: Ø56x25mm

Ordering example:

(1) (2) (3) (4) (5) (6) (7) (8) (9)
A 3 - M2 A - 4 a - NS - P sh

* Non-standard execution on special demand
Applied higher prices, possibility of increased minimum order quantity and extended production time.